

AGRIMAX RT 955 - Technical Specifications



Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Sprayer • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	230/95 R 36 (9.5 R 36)
LI/SS	130 A8/B

Dimensions International Standard

Section Width (mm)	228
Overall Diameter (mm)	1352
Static Loaded Radius (mm)	639
Rolling Circumference (mm)	4112
SRI (mm)	650
Rim Rec	W 7
Rim Alt	W 8
ECE	E4-106R-000765
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	745	970	1180	1295	1370	1505	1635	1770	1900	-
40	745	970	1180	1295	1370	1505	1635	1770	1900	-
30	795	1040	1265	1385	1470	1610	1755	1895	2035	-
10	885	1115	1370	1625	1885	1940	2170	2395	2625	2850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 3:19 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..