AGRIMAX SIRIO - Technical Specifications

Description

AGRIMAX SIRIO is a high-speed tire (up to 70 km/h - 45 mph) developed by BKT for high-performance tractors. Its design is perfect for both haulage and soil tillage applications. The high sidewall flexibility ensures outstanding stability, handling and comfort to improve the driving experience. It is also available with IF technology that allows to carry heavy loads at a low inflating pressure. The reinforced casing and the high number of belts guarantee great traction on the field whereas the low rolling resistance contributes to better fuel economy.

UM

US Standard

Construction

RADIAL

Machinery

Agriculture: High-Power Tractor

Version	HIGH SPEED
Type	TL
Tyre Size	IF 600/70 R 30
LI/SS	165 D/162 E

Dimensions US Standard

Usa code	94044849
Section Width (inch)	23.7
Overall Diameter (inch)	63.1
Static Loaded Radius (inch)	28.1
Rolling Circumference (inch)	187.4
Rim Rec	DW 21 B
Rim Alt	DW 20 B
ECE	E4-106R-000817
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	4850	5570	6400	7240	8050	8880	9590	10330
From 40 to 25	5340	6130	7040	7950	8860	9760	10550	11360
20	5550	6380	7310	8260	9210	10150	10970	11810
15	5660	6500	7460	8430	9390	10340	11180	12030
12	5760	6620	7600	8580	9560	10530	11390	12260
5	6770	7790	8930	10090	11240	12380	13400	14420

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 9:28 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..