

AGRIMAX SPARGO - Technical Specifications



Description

AGRIMAX SPARGO is the special BKT tire for row crop applications. It has been designed for enhanced productivity in the fields and for preserving the soil in the long term. Thanks to VF technology, the tire provides higher load capacity at standard pressure. Thanks to a strong casing and an increased number of lugs, AGRIMAX SPARGO ensures outstanding durability along with strong stability both in the fields and during road transfers.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer

Version	STANDARD
Type	TL
Tyre Size	VF 380/105 R 50
LI/SS	179 D

Dimensions International Standard

Section Width (mm)	400
Overall Diameter (mm)	2050
Static Loaded Radius (mm)	934
Rolling Circumference (mm)	6211
SRI (mm)	975
Rim Rec	W 13 A
Rim Alt	W 12 ; DW 12 ; DW 13 ; DW 13 L
ECE	E4-106R-002397
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4
70	3380	3805	4155	4370	4580	4720	4860	5145	5355	5565	5780	5990	6130	6345	6485	6765	7050
From 65 to 40	3720	4185	4570	4805	5035	5190	5345	5655	5890	6120	6355	6585	6740	6975	7130	7440	7550
30	3790	4265	4660	4990	5135	5295	5450	5770	6005	6240	6480	6715	6875	7110	7270	7585	7905
20	3865	4350	4755	4995	5235	5400	5560	5880	6125	6365	6605	6850	7010	7250	7415	7735	8060
10	4090	4600	5025	5285	5540	5710	5880	6220	6475	6730	6990	7245	7415	7670	7840	8180	8525

Printed on 4/17/2024 4:21 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..