

AGRIMAX SPARGO - Technical Specifications



Description

AGRIMAX SPARGO is the special BKT tire for row crop applications. It has been designed for enhanced productivity in the fields and for preserving the soil in the long term. Thanks to VF technology, the tire provides higher load capacity at standard pressure. Thanks to a strong casing and an increased number of lugs, AGRIMAX SPARGO ensures outstanding durability along with strong stability both in the fields and during road transfers.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer

Version	STANDARD
Type	TL
Tyre Size	VF 380/90 R 54
LI/SS	176 D

Dimensions International Standard

Section Width (mm)	383
Overall Diameter (mm)	2056
Static Loaded Radius (mm)	948
Rolling Circumference (mm)	6232
SRI (mm)	975
Rim Rec	W13
Rim Alt	DW 13 ; DW 12 ; W 12
ECE	E11-106R-0010081
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4
70	2825	3155	3550	3875	4075	4270	4400	5430	4760	4990	5190	5385	5550	5715	5880	6040	6305	6565
From 65 to 40	3055	3410	3835	4190	4405	4615	4760	4900	5150	5400	5610	5825	6000	6180	6355	6535	6820	7100
30	3120	3480	3915	4275	4495	4710	4855	5000	5255	5510	5725	5945	6125	6305	6485	6670	6960	7245
20	3180	3545	3990	4360	4580	4805	4950	5100	5355	5615	5835	6060	6245	6425	6610	6795	7090	7385
10	3360	3750	4220	4610	4845	5080	5235	5390	5665	5940	6170	6405	6600	6795	6990	7190	7500	7810

Printed on 4/29/2024 8:24 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..