

AGRIMAX SPARGO - Technical Specifications



Description

AGRIMAX SPARGO is the special BKT tire for row crop applications. It has been designed for enhanced productivity in the fields and for preserving the soil in the long term. Thanks to VF technology, the tire provides higher load capacity at standard pressure. Thanks to a strong casing and an increased number of lugs, AGRIMAX SPARGO ensures outstanding durability along with strong stability both in the fields and during road transfers.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer

Version	STANDARD
Type	TL
Tyre Size	VF 380/90 R 54
LI/SS	176 D

Dimensions US Standard

Usa code	94075614
Section Width (inch)	15.1
Overall Diameter (inch)	80.9
Static Loaded Radius (inch)	37.3
Rolling Circumference (inch)	245.4
Rim Rec	W13
Rim Alt	DW 13 ; DW 12 ; W 12
ECE	E11-106R-0010081
TRA Code	R1

Load capacity (lbs)

mph / psi	14	17	20	23	26	29	32	35	38	41	44	47	49	52	55	58	61	64
45	6230	6960	7830	8550	8990	9420	9700	9990	10500	11010	11450	11880	12240	12600	12970	13320	13900	14480
From 40 to 25	6740	7520	8460	9240	9720	10180	10500	10810	11360	11910	12370	12850	13230	13630	14010	14410	15040	15660
20	6880	7680	8640	9430	9910	10390	10710	11030	11590	12150	12630	13110	13510	13900	14300	14710	15350	15980
12	7020	7820	8800	9620	10100	10600	10920	11250	11810	12380	12870	13360	13770	14170	14580	14980	15630	16290
5	7410	8270	9310	10170	10690	11200	11550	11890	12490	13100	13610	14120	14550	14980	15410	15860	16540	17220

Printed on 4/30/2024 1:42 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..