

AGRIMAX TERIS - Technical Specifications



Description

Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations. Excellent traction properties and high load capacity are its essential features providing best performance in all harvesting operations. The special sidewall protection and a reinforced shoulder increase resistance - thus extending the product life-cycle - also in harsh conditions and if there are stubbles in the fields.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Cotton Picker • Harvester

Version	STANDARD
Type	TL
Tyre Size	620/75 R 30 CHO
LI/SS	168 A8/B

Dimensions International Standard

Section Width (mm)	625
Overall Diameter (mm)	1692
Static Loaded Radius (mm)	779
Rolling Circumference (mm)	5169
SRI (mm)	800
Rim Rec	DW 20 B
ECE	E4-106R-001420

Load capacity (Kg)

km/h / bar	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2
50	2580	2970	3640	3980	4370	4760	5155	5600
40	2580	2970	3640	3980	4370	4760	5155	5600
30	2760	3180	3900	4260	4680	5100	5520	5995
15 Cyc	4255	4900	6010	6565	7210	7855	8505	9240
10 Cyc	4640	5345	6555	7160	7865	8570	9275	10080

Printed on 11/29/2023 1:56 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..