

AGRIMAX TERIS - Technical Specifications



Description

Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations. Excellent traction properties and high load capacity are its essential features providing best performance in all harvesting operations. The special sidewall protection and a reinforced shoulder increase resistance - thus extending the product life-cycle – also in harsh conditions and if there are stubbles in the fields.

UM

US Standard

Construction



RADIAL

Machinery

Agriculture: Cotton Picker • Harvester

Version	STANDARD
Type	TL
Tyre Size	650/75 R 32 CHO
LI/SS	172 A8/B

Dimensions US Standard

Usa code	94032860
Section Width (inch)	26.4
Overall Diameter (inch)	70.7
Static Loaded Radius (inch)	32.1
Rolling Circumference (inch)	211.7
Rim Rec	DW 21 B
Rim Alt	DW 20 B ; DW 23 B
ECE	E4-106R-001425

Load capacity (lbs)

mph / psi	12	15	20	23	29	35	41	46
30	6390	7360	9030	9870	10840	11810	12790	13890
25	6390	7360	9030	9870	10840	11810	12790	13890
20	6840	7880	9670	10560	11610	12640	13690	14870
10 Cyc	10550	12150	14900	16280	17880	19490	21090	22920
5 Cyc	11510	13260	16260	17760	19510	21250	23000	25000

Printed on 4/26/2024 11:20 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..