

AGRIMAX V-FLECTO - Technical Specifications



Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the exclusive VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 710/60 R 34 NRO
LI/SS	173 D

Dimensions International Standard

Section Width (mm)	708
Overall Diameter (mm)	1716
Static Loaded Radius (mm)	752
Rolling Circumference (mm)	5097
SRI (mm)	825
Rim Rec	DW 25 B
Rim Alt	DW 24 B ; DW 27 B
ECE	E11-106R-007201
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	3020	3490	3965	4500	4910	5325	5915
From 65 to 40	3315	3835	4355	4940	5395	5850	6500
30	3385	3915	4445	5040	5505	5970	6630
20	3450	3990	4530	5140	5615	6085	6760
10	3650	4220	4795	5435	5935	6435	7150
10 Cyc	4645	5370	6100	6920	7555	8190	9100
10 HT	3385	3915	4445	5040	5505	5970	6630

* - For 10 Cyc application inflation pressure to be increased by 0.8 bar.

Printed on 4/2/2023 11:34 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..