

# AGRIMAX V-FLECTO - Technical Specifications



## Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 750/70 R 44
LI/SS	186 D

## Dimensions International Standard

Section Width (mm)	760
Overall Diameter (mm)	2175
Static Loaded Radius (mm)	958
Rolling Circumference (mm)	6450
SRI (mm)	1025
Rim Rec	DW 25 B
Rim Alt	DW 24 B
ECE	E11-106R-006765
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1	1.2	1.4	1.6	2
70	4325	5015	5710	6485	7180	7870	8645
from 65 to 40	4750	5510	6270	7125	7885	8645	9500
30	4845	5625	6400	7270	8045	8820	9690
20	4940	5735	6525	7410	8205	8995	9880
10	5225	6065	6900	7840	8675	9510	10450
*Upto 10 Cyc with front loader	6650	7715	8780	9975	11040	12105	13300
10HT	4845	5625	6400	7270	8045	8820	9690

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 4:49 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..