

AGRIMAXFACTOR - Data Sheet



Description

AGRIMAXFACTOR is BKT's brand-new 70 series for tractors that is perfect for both haulage and soil tillage operations. The improved tread design with further increased lug length and changed lug orientation stands for better roadability. The reduced lug angle ensures less rolling resistance, whilst the by 5 % increased contact area on the land significantly reduced the noise perception in the cabin – both features stand for more comfort. In addition, the strong polyester casing provides extraordinary lateral stability and a faster steering response even for high-speed operations or heavy-duty service. The tire's braking results on wet surface are excellent.

In a nutshell, AGRIMAXFACTOR's overall advantages are great handling in combination with under many aspects extraordinary driving comfort in addition to excellent durability – all particular requirements by increasingly heavier machinery including the higher weight of e-vehicles' battery packages. The exclusive sidewall shows the perfectly aligned "E-READY" logo that highlights BKT's commitment to electric mobility.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
380/70 R 24	STANDARD	R1W	125 D / 128A8	W 12	W 11 ; W 13	380	1190	538	3524	575	TL	E11-106R-007644
420/70 R 28	STANDARD	R1W	133 D/136 A8	W 13	W 12 ; W 14 L	418	1349	606	4000	650	TL	E11-106R-007652
480/70 R 28	STANDARD	R1W	140 D/143 A8	W 15 L	W 14 L ; W 16 L	479	1421	639	4239	675	TL	E11-106R-007610
600/70 R 28	STANDARD	R1W	157 D/160 A8	DW 20 B	DW 18 L ; W 18 L	611	1551	714	4667	725	TL	E11-106R-007655
600/70 R 30	STANDARD	R1W	152 D/155 A8	DW 20 B	DW 18 L ; W 18 L	611	1602	722	4765	750	TL	E11-106R-007524
480/70 R 34	STANDARD	R1W	149 D/152 A8	W 15 L	W 14 L ; W 16 L	479	1580	723	4748	750	TL	E11-106R-007642
480/70 R 38	STANDARD	R1W	145 D/148 A8	W 15 L	W 14 L ; W 16 L	479	1681	758	5000	800	TL	E11-106R-007654
520/70 R 38	STANDARD	R1W	150 D/153 A8	W 16 L	W 15 L ; W 18 L	516	1749	795	5239	825	TL	E11-106R-007609
580/70 R 38	STANDARD	R1W	155 D/158 A8	W 18 L	DW18L;DD18L	577	1827	823	5456	875	TL	E11-106R-007608
710/70 R 38	STANDARD	R1W	166 D/169 A8	DW 23 B		716	1959	866	5800	925	TL	E11-106R-007636
710/70 R 42	STANDARD	R1W	173 D/176 A8	DW 23 B	DW 25 B	716	2061	935	6166	975	TL	E11-106R-007526
710/70 R 42	STANDARD	R1W	176 D/179 A8	DW 23 B	DW 25 B	716	2061			975	TL	E11-106R-007525

Printed on 5/31/2023 10:34 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..