

AGRIMAXFACTOR - Data Sheet



Description

AGRIMAXFACTOR is BKT's brand-new 70 series for tractors that is perfect for both haulage and soil tillage operations. The improved tread design with further increased lug length and changed lug orientation stands for better roadability. The reduced lug angle ensures less rolling resistance, whilst the by 5 % increased contact area on the land significantly reduced the noise perception in the cabin – both features stand for more comfort. In addition, the strong polyester casing provides extraordinary lateral stability and a faster steering response even for high-speed operations or heavy-duty service. The tire's braking results on wet surface are excellent.

In a nutshell, AGRIMAXFACTOR's overall advantages are great handling in combination with under many aspects extraordinary driving comfort in addition to excellent durability – all particular requirements by increasingly heavier machinery including the higher weight of e-vehicles' battery packages. The exclusive sidewall shows the perfectly aligned "E-READY" logo that highlights BKT's commitment to electric mobility.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

SIZE	Version	USACode	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
380/70 R 24	STANDARD	94071012	R1W	125 D / 128A8	W 12	W 11 ; W 13	15	46.9	21.2	138.7	TL	E11-106R-007644
420/70 R 28	STANDARD	94070633	R1W	133 D/136 A8	W 13	W 12 ; W 14 L	16.5	53.1	23.9	157.5	TL	E11-106R-007652
480/70 R 28	STANDARD	94070718	R1W	140 D/143 A8	W 15 L	W 14 L ; W 16 L	18.9	55.9	25.2	166.9	TL	E11-106R-007610
600/70 R 28	STANDARD	94071135	R1W	157 D/160 A8	DW 20 B	DW 18 L ; W 18 L	24.1	61.1	28.1	183.7	TL	E11-106R-007655
600/70 R 30	STANDARD	94070152	R1W	152 D/155 A8	DW 20 B	DW 18 L ; W 18 L	24.1	63.1	28.4	187.6	TL	E11-106R-007524
480/70 R 34	STANDARD	94071029	R1W	149 D/152 A8	W 15 L	W 14 L ; W 16 L	18.9	62.2	28.5	186.9	TL	E11-106R-007642
480/70 R 38	STANDARD	94071043	R1W	145 D/148 A8	W 15 L	W 14 L ; W 16 L	18.9	66.2	29.8	196.9	TL	E11-106R-007654
520/70 R 38	STANDARD	94070725	R1W	150 D/153 A8	W 16 L	W 15 L ; W 18 L	20.3	68.9	31.3	206.3	TL	E11-106R-007609
580/70 R 38	STANDARD	94071050	R1W	155 D/158 A8	W 18 L	DW18L;DD18L	22.7	71.9	32.4	214.8	TL	E11-106R-007608
710/70 R 38	STANDARD	94071142	R1W	166 D/169 A8	DW 23 B		28.2	77.1	34.1	228.3	TL	E11-106R-007636
710/70 R 42	STANDARD	94070169	R1W	173 D/176 A8	DW 23 B	DW 25 B	28.2	81.1	36.8	242.8	TL	E11-106R-007526
710/70 R 42	STANDARD	94070527	R1W	176 D/179 A8	DW 23 B	DW 25 B	28.2	81.1	0	0	TL	E11-106R-007525

Printed on 5/31/2023 9:28 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..