

AIROMAX AM 543 - Data Sheet



Description

AIROMAX AM 543 is the ideal tire for construction applications with cranes. It shows outstanding traction and high stability. As crane tires are subject to particular stress and extreme usage conditions, AIROMAX AM 543 has been designed for providing excellent heat resistance. Besides, it is suitable for all operations requiring a high level of handling.

UM

US Standard

Construction



RADIAL

Machinery

Industrial: Mobile Crane

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
385/95 R 24 (14.00 R 24)	STANDARD	94064502	170 E	10.00W		14.8	53.3	24.7	163.6	TT
385/95 R 25 (14.00 R 25)	STANDARD	94064519	170 E	10.00/1.5		14.8	53.3	24.7	163.6	TL
445/95 R 25 (16.00 R 25)	STANDARD	94036660	177 E	11.25/2.0	11.00/1.7 CR ; 11.00/1.7CRL	17.1	58.3	26.4	177.2	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 1:53 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..