AT 111 HD - Data Sheet

Description

AT 111 HD is suitable for all-terrain sport racing with ATVs. The increased tread depth and the thick sidewall provide extra grip and braking control in addition to extraordinary traction and high-speed control in power slides. AT 111 HD ensures an extended tire life-cycle.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: ATV

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
AT 20 X 11 - 9	STANDARD	43 J	6	9.0 AT	8.5 AT	275	515	TL	E4-75R-0006326
AT 22 X 11 - 9	STANDARD		6	9.0 AT	8.5 AT	279	560	TL	E4-75R-0006332
AT 20 X 11 - 10	STANDARD		6	9.0 AT	8.5 AT	279	505	TL	E4-75R-0006327
AT 21 X 7 - 10	STANDARD	30 J	6	5.5 AT	6.0 AT	178	533	TL	E4-75R-0006329
AT 22 X 11 - 10	STANDARD		6	9.0 AT	8.5 AT	279	560	TL	E4-75R-0006333
AT 22 X 7 - 10	STANDARD		6	5.5 AT	6.0 AT	174	560	TL	E4-75R-0006331
AT 23 X 7 - 10	STANDARD		6	5.5 AT	6.0 AT	174	585	TL	E4-75R-0006335

Printed on 4/18/2024 10:13 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..