

## AT 171 - Technical Specifications



### Description

AT 171 has been specifically designed for mud bogger tractors. The special directional and extra-deep tread design provides excellent traction on wet and muddy surfaces.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: ATV • Mud Bogger Tractor

Version	STANDARD
Type	TL
Tyre Size	AT 40 X 10 - 22
LI/SS	95 A8 / 71 F

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	235
Overall Diameter (mm)	1005
Static Loaded Radius (mm)	469
Rolling Circumference (mm)	2955
Rim Rec	W 8
Rim Alt	W 7
TRA Code	R1W+

## Load capacity (Kg)

km/h / bar	1.40	1.00
40 MUD BOGGING	690	-
80 MUD BOGGING	345	-
40 CASUAL TRANSPORT	-	565
80 CASUAL TRANSPORT	-	285

Printed on 4/13/2024 5:53 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..