



## AT 603 - Data Sheet



### Description

AT 603 is a bias agro-industrial tire for implement machinery and backhoe loaders. AT 603 has been engineered to ensure great durability and traction on drive wheels providing best performance on every surface as well as excellent self-cleaning properties. The AT 603 "special" version has a reinforced casing, while the "HD" version offers improved cut and chip resistance.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Backhoe Loader • Implement Machinery  
Industrial: Backhoe Loader

| SIZE         | Version  | USACode  | TRA Code | LI/SS DRIVE WHEEL | LI/SS FREE ROLLING | PR | RIM REC   | RIM ALT        | SW   | OD   | SLR  | RC    | Type | ECE             |
|--------------|----------|----------|----------|-------------------|--------------------|----|-----------|----------------|------|------|------|-------|------|-----------------|
| 10.5/80 - 18 | HD       | 94032570 |          | 119 A8            | 131 A8             | 10 | W 9       | W 8 ; 9        | 10.8 | 35.7 | 16.6 | 107.4 | TL   | E11-106R-004546 |
| 10.5/80 - 18 | SPECIAL  | 94019670 |          | 119 A8            | 131 A8             | 10 | W 9       | W 8 ; 9        | 10.8 | 35.7 | 16.6 | 107.4 | TL   | E11-106R-004546 |
| 10.5/80 - 18 | STANDARD | 94019526 |          | 119 A8            | 131 A8             | 10 | W 9       | W 8 ; 9        | 10.8 | 35.7 | 16.6 | 107.4 | TL   | E4-106R-002325  |
| 12.5/80 - 18 | SPECIAL  | 94033904 |          | 129 A8            | 142 A8             | 12 | W 9       | 11             | 12.1 | 38.9 | 17.6 | 119.2 | TL   | E4-106R-004350  |
| 12.5/80 - 18 | STANDARD | 94019595 |          | 129 A8            | 142 A8             | 12 | W 9       | 11             | 12.1 | 38.9 | 17.6 | 119.2 | TL   |                 |
| 12.5/80 - 18 | STANDARD | 94019663 |          | 135 A8            | 148 A8             | 16 | W 9       | 11             | 12.1 | 38.9 | 17.6 | 119.2 | TL   | E11-106R-004351 |
| 12.5/80 - 18 | STANDARD | 94031269 |          | 138 A8            | 150 A8             | 18 | W 9       | 11             | 12.1 | 38.9 | 17.6 | 119.2 | TL   | E11-106R-004352 |
| 15.5 - 25    | STANDARD | 94059775 | E2/G2/L2 |                   |                    | 12 | 12.00/1.3 | 12.00/1.3 (DC) | 16.1 | 49.8 | 22.7 | 152   | TL   |                 |

Printed on 2/3/2023 5:52 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..