

## AT 625 - Technical Specifications



### Description

The **AT 625** tire is designed for backhoe loaders and compact loaders, excelling in all farming, digging, and loading operations. It's also an ideal choice for sugarcane harvesting, offering the reliability needed to keep you productive throughout the season. With its extra deep tread, the AT 625 ensures increased puncture resistance and durability, allowing you to tackle tough conditions with confidence. This tire delivers outstanding traction and stability, combined with enhanced cut and chip resistance, making it a durable and dependable partner for your agricultural tasks.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Harvester

Industrial: Backhoe Loader • Compact Loader

Version	STANDARD
Type	TL
Tyre Size	14.9 - 24
LI/SS	145 A8

## Dimensions US Standard

Usa code	94051007
Ply Rating	12
Section Width (inch)	15.7
Overall Diameter (inch)	49.8
Static Loaded Radius (inch)	22.6
Rolling Circumference (inch)	149.6
Rim Rec	DW 13
Rim Alt	DW 11 ; DW 12 ; DW 13 L
TRA Code	R4

## Load capacity (lbs)

mph / psi	42
25	6400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 6:17 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..