

AW 909 - Technical Specifications



Description

AW 909 has been developed for soil tillage, hay harvesting and transport applications with implement machinery, trailers and balers. It is ideal for modern farming both on and off the road.

UM

US Standard

Construction

✚ BIAS

Machinery

Agriculture: Baler • Implement Machinery • Trailer

Version	STANDARD
Type	TL
Tyre Size	10.0 / 75 - 12
LI/SS FREE ROLLING	116 A8

Dimensions US Standard

Usa code	94044870
Ply Rating	8
Section Width (inch)	10.4
Overall Diameter (inch)	28
Static Loaded Radius (inch)	12.3
Rolling Circumference (inch)	81.9
Rim Rec	9.00
Rim Alt	7.0
ECE	E11-106R-005258

Load capacity (lbs)

mph / psi	45
5 FR	3860
15 FR	3280
20 FR	3090
25 FR	2760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 2:14 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..