

# COMMANDER TWIN RIB - Technical Specifications



## Description

COMMANDER TWIN RIB is a 4-rib pattern tire with shoulder notches providing excellent grip. Its wider tread profile ensures good weight distribution. The strong casing along with a superior tread compound provide a longer tire life. COMMANDER TWIN RIB is perfect for soil tillage and haulage applications.

## UM

US Standard

## Construction

 BIAS

## Machinery

Agriculture: 2WD Tractor

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TT        |
| Tyre Size | 6.50 - 20 |
| LI/SS     | 93 A8     |

## Dimensions US Standard

|                         |                 |
|-------------------------|-----------------|
| Usa code                | 94054015        |
| Ply Rating              | 8               |
| TMPH                    | 1               |
| Section Width (inch)    | 7.5             |
| Overall Diameter (inch) | 34.4            |
| Rim Rec                 | 5.00 F          |
| Rim Alt                 | 4.00 E ; 5.50 F |
| ECE                     | E11-106R-004258 |
| TRA Code                | F2              |

## Load capacity (lbs)

|           |      |
|-----------|------|
| mph / psi | 66   |
| 25        | 1440 |

Printed on 12/6/2023 10:40 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..