

## CON STAR - Technical Specifications



### Description

CON STAR is particularly suitable for compact loaders and telehandlers in agro-industrial, lifting and loading applications. It features great traction along with excellent vertical and horizontal stability. CON STAR has been made of a cut-and-chip-resistant compound contributing to an extended tire life-cycle.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Compact Loader • Telehandler

Industrial: Compact Loader • Telehandler

Version	INDUSTRIAL
Type	TL
Tyre Size	380/75 - 20 (14.5 - 20)
LI/SS	148 A8

## Dimensions International Standard

Section Width (mm)	385
Overall Diameter (mm)	1080
Static Loaded Radius (mm)	500
Rolling Circumference (mm)	3273
Rim Rec	W 12
Rim Alt	W 11 ; 12 SDC ; 12 ; W 13 ; 13 SDC ; 13
ECE	E11-106R-003022

## Load capacity (Kg)

km/h / bar	4.00
40	3150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 10:40 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..