

## CONTAINER KING - Technical Specifications



### Description

CONTAINER KING has been designed for reach stackers in intermodal transport and logistics applications. This extraordinary tire is made of a highly wear-and-tear-resistant tread compound which minimizes tread cracks. CONTAINER KING ensures an extended tire life-cycle plus exceptional stability in lift mode.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Reach Stacker

Version	INDUSTRIAL
Type	TT
Tyre Size	12.00 - 24

## Dimensions International Standard

Ply Rating	24
Overall Width (mm)	330
Overall Diameter (mm)	1285
Rim Rec	8.5
Rim Alt	8.0
TRA Code	IND4

## Load capacity (Kg)

km/h / bar	10.00
10	10270

Printed on 4/26/2024 9:43 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..