

DESERT KING - Technical Specifications



Description

DESERT KING is best suited for loose soil, sandy terrain and paver applications with desert trucks. The optimized rib tread design offers excellent flotation and directional stability. Its strong nylon casing and heavy-duty bead are specially developed for low pressure operations. DESERT KING provides also high punctures resistance and a longer tire life.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Desert Truck

| | |
|-----------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 21.00 - 25 DT |

Dimensions International Standard

| | |
|----------------------------|-----------|
| Ply Rating | 16 |
| Section Width (mm) | 570 |
| Overall Diameter (mm) | 1660 |
| Static Loaded Radius (mm) | 708 |
| Rolling Circumference (mm) | 4906 |
| Rim Rec | 15.00/3.0 |
| TRA Code | E7 |

Load capacity (Kg)

| | |
|------------|------|
| km/h / bar | 2.50 |
| 10 | 9750 |
| 50 | 6700 |
| 65 | 5600 |

Printed on 4/25/2024 8:15 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..