

# **DON 2000 - Technical Specifications**



### Description

DON 2000 is a suitable for transport operations with trailers and light trucks both on and off the road. It ensures extra durability along with high performance during the entire product life-cycle.

#### UM

International Standard

### Construction

BIAS

## Machinery

Agriculture: Light Truck • Trailer

Version	STANDARD
Туре	Π
Tyre Size	12.00 - 24

## **Dimensions International Standard**

Ply Rating	18
Section Width (mm)	315
Overall Diameter (mm)	1245
Rim Rec	8.5
Rim Alt	8.0 ; 9.0

# Load capacity (Kg)

km/h / bar	7.95	7.25
100 LS	4250	-
100 LD	-	3750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

#### Printed on 5/3/2025 9:05 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..