

EARTHMAX CRUSHER HAUL - Technical Specifications



Description

EARTHMAX CRUSHER HAUL is an All Steel radial tire designed for transport applications, both on and off the road, as well as mining operations. It features enhanced durability and mileage along with high load capacity thanks to the strong steel-belted construction and casing. The block-type tread pattern provides excellent traction. In addition, EARTHMAX CRUSHER HAUL ensures excellent riding comfort, less driving fatigue and superior handling.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: On/Off Truck

| | |
|-----------|------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 11.00 R 20 |
| LI/SS | 152/149 J |

Dimensions International Standard

| | |
|-----------------------|------|
| Ply Rating | 18 |
| Overall Width (mm) | 290 |
| Overall Diameter (mm) | 1102 |
| Rim Rec | 8.00 |
| Rim Alt | 8.50 |

Load capacity (Kg)

| | km/h / bar | 8.30 |
|-----------------|------------|------|
| 100 Load Single | | 3550 |
| 100 Load Dual | | 3250 |

Printed on 4/27/2024 7:41 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..