

# EARTHMAX SR 22 AS - Technical Specifications



## Description

EARTHMAX SR 22 AS (E-2\*\*/G-2\*/L-2\*\*) is an All Steel radial tire specially designed for graders, small loaders and trucks operating on ice and snow ensuring also optimum performance in all-season conditions.

The extraordinary tread design features deep sipes and a four-block pattern. Made of unique winter compounds, it provides superior braking performance in icy or snowy conditions and avoids stone trapping during all-season usage.

The low void ratio and wide footprint of EARTHMAX SR 22 AS stand for excellent traction and stability with even wear, and a long tread life.

## UM

International Standard

## Construction

 RADIAL

## Machinery

OTR: Grader • Loader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	17.5 R 25
LI/SS	167 B/153 A8/182 A2

## Dimensions International Standard

Overall Width (mm)	445
Overall Diameter (mm)	1350
Static Loaded Radius (mm)	595
Rolling Circumference (mm)	4010
Rim Rec	14.00/1.5
Star Rating	**/*/**
TRA Code	E2/G2/L2

## Load capacity (Kg)

km/h / bar	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50
50	-	-	-	-	-	-	-	-	4375	4625	4750	5000	5150	5450	-	-	-	-	-
40	1850	2120	2360	2650	2900	3075	03350	3650	-	-	-	-	-	-	-	-	-	-	-
10	-	-	-	-	-	-	-	-	-	-	-	-	-	7300	7500	7750	8000	8250	8500

Printed on 4/24/2024 8:27 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..