

EARTHMAX SR 22 AS - Technical Specifications



Description

EARTHMAX SR 22 AS (E-2**/G-2*/L-2**) is an All Steel radial tire specially designed for graders, small loaders and trucks operating on ice and snow ensuring also optimum performance in all-season conditions.

The extraordinary tread design features deep sipes and a four-block pattern. Made of unique winter compounds, it provides superior braking performance in icy or snowy conditions and avoids stone trapping during all-season usage.

The low void ratio and wide footprint of EARTHMAX SR 22 AS stand for excellent traction and stability with even wear, and a long tread life.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Grader • Loader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	23.5 R 25
LI/SS	185 B/170 A8 /201 A2

Dimensions International Standard

Overall Width (mm)	610
Overall Diameter (mm)	1614
Static Loaded Radius (mm)	709
Rolling Circumference (mm)	4863
Rim Rec	19.50/2.5
Star Rating	**/**/**
TRA Code	E2/G2/L2
Tread Depth	34

Load capacity (Kg)

km/h / bar	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50
50	-	-	-	-	-	-	-	-	7500	7750	8250	8500	9000	9250	-	-	-	-	-
40	3150	3550	4000	4500	4875	5300	5600	6000	-	-	-	-	-	-	-	-	-	-	-
10	-	-	-	-	-	-	-	-	-	-	-	-	-	12500	12850	13200	13600	14000	14500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 9:49 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..