

## EARTHMAX SR 31 - Data Sheet



### Description

EARTHMAX SR 31 is an All Steel radial tire specially designed for articulated dump trucks and wheel loaders. Its multiply steel belts provide extraordinary strength and stability, whilst the non-directional rigid block pattern stands for both excellent traction and maneuverability even on muddy ground. In addition to outstanding riding comfort, EARTHMAX SR 31 features a special tread compound which is particularly cut-and-heat resistant. The radial casing structure also provides reduced rolling resistance offering significant fuel savings.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Industrial: Dozer • Loader

OTR: Articulated Dump Truck (ADT) • Dozer • Loader

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
20.5 R 25	CUT RESISTANT COMPOUND	E3/L3	**/*	177 B/186 A2	17.00/2.0	--	540	1480	663	4449	TL	170
23.5 R 25	CUT RESISTANT COMPOUND	E3/L3	**/*	185 B/195 A2	19.50/2.5	-	612	1607	711	4797	TL	200
26.5 R 25	CUT RESISTANT COMPOUND	E3/L3	**/*	193 B/202 A2	22.00/3.0		689	1742	766	5200	TL	230
26.5 R 25	CUT RESISTANT COMPOUND	L3	**	209 A2	22.00/3.0		689	1742	766	5200	TL	
29.5 R 25	CUT RESISTANT COMPOUND	E3/L3	**/*	200 B/208 A2	25.00/3.5		765	1861	818	5555	TL	270
29.5 R 25	CUT RESISTANT COMPOUND	L3	**	216 A2	25.00/3.5		765	1861	818	5555	TL	

Printed on 3/31/2023 1:39 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..