

## EARTHMAX SR 31 - Data Sheet



### Description

EARTHMAX SR 31 is an All Steel radial tire specially designed for articulated dump trucks and wheel loaders. Its multiple steel belts provide extraordinary strength and stability, whilst the non-directional rigid block pattern stands for both excellent traction and maneuverability even on muddy ground. In addition to outstanding riding comfort, EARTHMAX SR 31 features a special tread compound which is particularly cut-and-heat resistant. It provides excellent riding comfort in 'Load and Carry' operations on hard improved surfaces. The radial casing structure also delivers reduced rolling resistance offering significant fuel savings.

### UM

US Standard

### Construction



RADIAL

### Machinery

Industrial: Dozer • Loader

OTR: Articulated Dump Truck (ADT) • Dozer • Loader

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth	TMPH
20.5 R 25	CUT RESISTANT COMPOUND	94060610	E3/L3	**/*	177 B/186 A2	17.00/2.0	--	21.3	58.3	26.1	175.2	TL	40	116
23.5 R 25	CUT RESISTANT COMPOUND	94048434	E3/L3	**/*	185 B/195 A2	19.50/2.5	-	24.1	63.3	28	188.9	TL	43	137
26.5 R 25	CUT RESISTANT COMPOUND	94053735	E3/L3	**/*	193 B/202 A2	22.00/3.0		27.1	68.6	30.2	204.7	TL	48	158
26.5 R 25	CUT RESISTANT COMPOUND	94054381	L3	**	209 A2	22.00/3.0		27.1	68.6	30.2	204.7	TL	48	0
29.5 R 25	CUT RESISTANT COMPOUND	94053742	E3/L3	**/*	200 B/208 A2	25.00/3.5		30.1	73.3	32.2	218.7	TL	53	185
29.5 R 25	CUT RESISTANT COMPOUND	94054398	L3	**	216 A2	25.00/3.5		30.1	73.3	32.2	218.7	TL	53	0

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 4:55 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..