



## EARTHMAX SR 32 - Data Sheet



### Description

EARTHMAX SR 32 is a non-directional wide-base radial tire particularly suitable for scrapers. The tire features a strong All Steel casing and a special tread compound providing excellent cut and puncture resistance as well as durability. Additional traits are exceptional traction and flotation even during heavy-duty operations.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Scraper

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
<b>29.5 R 29</b>	CUT RESISTANT COMPOUND	94066216	E3	**	202 B	25.00/3.5	24.00/3.5	30.1	78	34.8	236.6	TL	197
<b>33.25 R 29</b>	CUT RESISTANT COMPOUND	94057986	E3	**	209 B	27.00/3.5	26.00/3.5	33.3	81.9	36	246.1	TL	237
<b>37.25 R 35</b>	CUT RESISTANT COMPOUND	94064243	E3	**	218 B	31.00/4.0		37.9	93.7	41.8	284.6	TL	310
<b>40.5/75 R 39</b>	CUT RESISTANT COMPOUND	94066506	E3	**	225 B	32.00/4.5		38.8	102.8	45.8	312	TL	346
<b>40.5/75 R 39</b>	STANDARD COMPOUND	94069392	E3	**	225 B	32.00/4.5		38.8	102.8	45.8	312	TL	472

Printed on 4/20/2024 4:29 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..