



EARTHMAX SR 412 - Data Sheet



Description

EARTHMAX SR 412 (E-4/L-4) is an All Steel radial tire specially designed for Articulated Dump Trucks, Loaders and Dozers. The unique E-4 deep tread pattern ensures excellent traction and exceptional heat resistance. Thanks to its strong All Steel casing and belts, EARTHMAX SR 412 can carry heavy loads providing excellent stability as well as best resistance to snags and punctures. EARTHMAX SR 412 features a squared shoulder design that maximizes ground contact for excellent maneuverability.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Articulated Dump Truck (ADT) • Dozer • Loader

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
29.5 R 25	CUT RESISTANT COMPOUND	94062836	E4	**	200 B	25.00/3.5		30.1	73.4	32.8	218.2	TL	173
750/65 R 25 (30/65 R 25)	CUT RESISTANT COMPOUND	94065233	E4/L4	**/*	190 B/202 A2	24.00/3.0	22.00/3.0, 25.00/3.0	30.7	63.1	28.1	190.5	TL	157
750/65 R 25 (30/65 R 25)	CUT RESISTANT COMPOUND	94064144	E4	**	190 B	24.00/3.0	22.00/3.0; 25.00/3.0	30.7	63.1	28.1	190.5	TL	157
800/65 R 29	CUT RESISTANT COMPOUND	94070572	E4/L4	**/*	198 B / 208 A2	27.00/3.0	24.00/3.5, 25.00/3.5	31.1	71.1	32.5	216.1	TL	141

Printed on 4/19/2024 8:56 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..