

# EARTHMAX SR 42 - Technical Specifications



## Description

EARTHMAX SR 42 is a radial OTR tire specially engineered for haul trains in mining and logging applications. The distinctive tread design provides outstanding traction and lateral stability as well as good braking and cornering performance on rough and gravel terrains even on ice and snow. Indeed, the special cut-and-wear-resistant tread compound is particularly suitable in extreme cold climate. EARTHMAX SR 42 features an All Steel casing for excellent durability and a long service life.

## UM

US Standard

## Construction

 RADIAL

## Machinery

OTR: Haul Train

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	14.00 R 25
LI/SS	171 B

## Dimensions US Standard

Usa code	94067190
TMPH	72
Overall Width (inch)	15
Overall Diameter (inch)	55.6
Static Loaded Radius (inch)	25.7
Rolling Circumference (inch)	166.6
Rim Rec	10.00/2.0
Rim Alt	--
Star Rating	***
TRA Code	E4

## Load capacity (lbs)

mph / psi	102	116
30	12800	13600

Printed on 4/27/2024 6:08 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..