

EARTHMAX SR 45 PLUS - Data Sheet



Description

EARTHMAX SR 45 PLUS is an All Steel radial tire specially designed for rigid haul trucks. It is ideal for operations in long hauls. The tread pattern of the EARTHMAX SR 45 PLUS minimizes vibration and noise.

UM

International Standard

Construction



RADIAL

Machinery

OTR: Rigid Dump Truck

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth	TKPH
27.00 R 49	CUT RESISTANT COMPOUND	E4	**	223 B	19.50/4.0	--	746	2702	1214	8095	TL	73	440
27.00 R 49	HEAT RESISTANT COMPOUND	E4	**	223 B	19.50/4.0	--	746	2702	1214	8095	TL	73	654
27.00 R 49	STANDARD COMPOUND	E4	**	223 B	19.50/4.0	--	746	2702	1214	8095	TL	73	540
33.00 R 51	CUT RESISTANT COMPOUND	E4	**	235 B	24.00/5.0		910	3065	1369	9313	TL	90	605
33.00 R 51	HEAT RESISTANT COMPOUND	E4	**	235 B	24.00/5.0		910	3065	1369	9313	TL	90	815
33.00 R 51	STANDARD COMPOUND	E4	**	235 B	24.00/5.0		910	3065	1369	9313	TL	90	705

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 2:53 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..