

## EARTHMAX SR 45 PLUS - Data Sheet



### Description

EARTHMAX SR 45 PLUS is an All Steel radial tire specially designed for rigid haul trucks. It is ideal for operations in long hauls. The tread pattern of the EARTHMAX SR 45 PLUS minimizes vibration and noise.

### UM

US Standard

### Construction



RADIAL

### Machinery

OTR: Rigid Dump Truck

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth	TMPH
<b>27.00 R 49</b>	CUT RESISTANT COMPOUND	94045655	E4	**	223 B	19.50/4.0	--	29.4	106.4	47.8	318.7	TL	92	301
<b>27.00 R 49</b>	HEAT RESISTANT COMPOUND	94049813	E4	**	223 B	19.50/4.0	--	29.4	106.4	47.8	318.7	TL	92	448
<b>27.00 R 49</b>	STANDARD COMPOUND	94049806	E4	**	223 B	19.50/4.0	--	29.4	106.4	47.8	318.7	TL	92	370
<b>33.00 R 51</b>	CUT RESISTANT COMPOUND	94073306	E4	**	235 B	24.00/5.0		35.8	120.7	53.9	366.7	TL	113	414
<b>33.00 R 51</b>	HEAT RESISTANT COMPOUND	94073320	E4	**	235 B	24.00/5.0		35.8	120.7	53.9	366.7	TL	113	558
<b>33.00 R 51</b>	STANDARD COMPOUND	94073313	E4	**	235 B	24.00/5.0		35.8	120.7	53.9	366.7	TL	113	483

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 6:30 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..