



## EARTHMAX SR 454 - Data Sheet



### Description

EARTHMAX SR 454 is an All Steel radial tire specially engineered for rigid dump trucks. The unique E-3 tread design and the special center groove provide enhanced lateral tractions and handling both on soft and muddy surfaces. This tire is specially designed for higher speeds, long hauls at cooler operating temperature. The All Steel construction with multi-layer steel belts provide superior protection against shock and rock penetration, to enhance uptime for a consequently higher productivity. The squared shoulder of EARTHMAX SR 454 maximizes ground contact for excellent maneuverability and stability, not to mention a minimized vibration and noise.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Rigid Dump Truck

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
27.00 R 49	CUT RESISTANT COMPOUND	E3	**	223 B	19.50/4.0	--	740	2650	1187	8040	TL	525
27.00 R 49	HEAT RESISTANT COMPOUND	E3	**	223 B	19.50/4.0	--	740	2650	1187	8040	TL	725
27.00 R 49	STANDARD COMPOUND	E3	**	223 B	19.50/4.0	--	740	2650	1187	8040	TL	640
33.00 R 51	CUT RESISTANT COMPOUND	E3	**	235 B	24.00/5.0		900	2990	1358	9085	TL	884
33.00 R 51	HEAT RESISTANT COMPOUND	E3	**	235 B	24.00/5.0		900	2990	1358	9085	TL	1215
33.00 R 51	STANDARD COMPOUND	E3	**	235 B	24.00/5.0		900	2990	1358	9085	TL	1023
40.00 R 57	CUT RESISTANT COMPOUND	E3	**	250 B	29.00/6.0	32.00/6.0	1115	3510	1583	10654	TL	1201
40.00 R 57	HEAT RESISTANT COMPOUND	E3	**	250 B	29.00/6.0	32.00/6.0	1115	3510	1583	10654	TL	1740
40.00 R 57	STANDARD COMPOUND	E3	**	250 B	29.00/6.0	32.00/6.0	1115	3510	1583	10654	TL	1462

Printed on 4/26/2024 6:25 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..