

EARTHMAX SR 46 - Technical Specifications



Description

Earthmax SR 46 for rigid haul trucks is BKT's innovative response to severe rocky, abrasive and harsh mining environments. This tire has been specifically designed to carry heavy loads offering superior resistance to cuts and chips as well as a long tire life-cycle. The All Steel casing and belts provide extraordinary protection against shocks, fatigue and flats to maximize uptime and enhance productivity. Earthmax SR 46 features a special lug block pattern with circumferential groove to optimize the cornering performance with minimum tread face damage.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Rigid Dump Truck

Version	HEAT RESISTANT COMPOUND
Type	TL
Tyre Size	33.00 R 51
LI/SS	235 B

Dimensions US Standard

Usa code	94067350
TMPH	548
Overall Width (inch)	35.6
Overall Diameter (inch)	120.1
Static Loaded Radius (inch)	55.2
Rolling Circumference (inch)	369.2
Rim Rec	24.00/5.0
Star Rating	**
TRA Code	E4

Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	66000	68000	71500	74000	76000	78500	80500	82500	85500

Printed on 4/18/2024 10:51 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..