

## EARTHMAX SR 48 - Technical Specifications



### Description

EARTHMAX SR 48 is an All Steel radial tire specially conceived and engineered for rigid haul trucks. It ensures enhanced traction and extraordinary tread resistance even for the most demanding operations in rocky environments. This tire is ideal for handling heavy loads. The square shoulder design protects the sidewall against cuts and damage. EARTHMAX SR 48 has a strong All Steel casing which provides exceptional protection against shocks and rock perforation resulting in enhanced productivity.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Rigid Dump Truck

|           |                         |
|-----------|-------------------------|
| Version   | HEAT RESISTANT COMPOUND |
| Type      | TL                      |
| Tyre Size | 27.00 R 49              |
| LI/SS     | 223 B                   |

## Dimensions US Standard

|                              |           |
|------------------------------|-----------|
| Usa code                     | 94054312  |
| TMPH                         | 411       |
| Overall Width (inch)         | 29.1      |
| Overall Diameter (inch)      | 105.8     |
| Static Loaded Radius (inch)  | 48.2      |
| Rolling Circumference (inch) | 321.5     |
| Rim Rec                      | 19.50/4.0 |
| Rim Alt                      | --        |
| Star Rating                  | **        |
| TRA Code                     | E4        |

## Load capacity (lbs)

| mph / psi | 73    | 76    | 80    | 83    | 87    | 91    | 94    | 98    | 102   |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30        | 45400 | 48100 | 49400 | 50700 | 52000 | 55100 | 56800 | 58400 | 60000 |

Printed on 4/20/2024 6:06 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..