



## EARTHMAX SR 50 - Data Sheet

### Description

EARTHMAX SR 50 (L-5) is an **All Steel** radial tire specially designed for loaders. The durable casing and sidewall protectors are ideal for the most demanding operations. EARTHMAX SR 50 is made of a special cut-resistant compound which ensures a long wear life. Operators will also appreciate its excellent traction, stability and comfortable ride.



### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Loader

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
26.5 R 25	CUT RESISTANT COMPOUND	94032303	L5	*	202 A2	22.00/3.0		27.2	69.8	31.7	210	TL
26.5 R 25	CUT RESISTANT COMPOUND	94037070	L5	**	209 A2	22.00/3.0		27.2	69.8	31.7	210	TL
29.5 R 25	CUT RESISTANT COMPOUND	94037230	L5	*	208 A2	25.00/3.5		30.5	74.8	33.9	225.3	TL
29.5 R 25	CUT RESISTANT COMPOUND	94069637	L5	**	216 A2	25.00/3.5		30.5	74.8	33.9	225.3	TL

Printed on 4/26/2024 9:30 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..