

# EARTHMAX SR 51 - Technical Specifications

## Description

EARTHMAX SR 51 (L-5) is an **All Steel** radial tire specially designed for loaders or dozers. EARTHMAX SR 51 is ideal for severe operations requiring added cut resistance, sidewall protection and exceptional traction.

## UM

US Standard

## Construction

 RADIAL

## Machinery

OTR: Dozer • Loader



Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	875/65 R 29 (35/65 R 29)
LI/SS	221 A2

Dimensions US Standard

Usa code	94067145
Overall Width (inch)	34.6
Overall Diameter (inch)	73.7
Static Loaded Radius (inch)	32
Rolling Circumference (inch)	221.1
Rim Rec	27.00/3.5
Rim Alt	27.00/3.0; 28.00/3.5
Star Rating	**
TRA Code	L5

Load capacity (lbs)

mph / psi	73	76	80	83	87	91
5	48100	50700	52000	53600	55100	56800

Printed on 4/24/2024 1:29 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..