

## EM 936 SUPER - Data Sheet



### Description

EM 936 SUPER has been specifically designed for excavators and telehandlers in digging and loading operations as well as transport applications. With increased tread width by 8-10%, EM 936 SUPER offers outstanding stability and enhanced riding comfort. It also ensures a high level of handling comfort and provides excellent traction even under heavy-duty service conditions.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Excavator

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
10.00 - 20	STANDARD	E2	145 B	14	7.5	7.0 ; 8.0	277	1080	500	3336	TT
10.00 - 20	STANDARD	E2	146 B	16	7.5	7.0 ; 8.0	277	1080	500	3336	TT

Printed on 5/7/2024 10:37 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..