

F 240 - Technical Specifications



Description

F 240 is a forestry tire designed for logging applications. Its tread pattern provides excellent traction, self-cleaning properties in addition to good steering. The superior tread compound ensures extraordinary cut-and-wear resistance resulting in a longer service life. F 240 shows a large contact area for better stability.

UM

US Standard

Construction

✚ BIAS

Machinery

Agriculture: Log Skidder

Version	STANDARD
Type	TT
Tyre Size	18 - 15.5

Dimensions US Standard

Usa code	94052004
Ply Rating	14
Section Width (inch)	17.7
Overall Diameter (inch)	39
Static Loaded Radius (inch)	16.9
Rolling Circumference (inch)	115.4
Rim Rec	AG 13.00
ECE	E11-106R-004259
TRA Code	LS2

Load capacity (lbs)

mph / psi	50
20	9225

Printed on 4/17/2024 5:30 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..