

FL 252 - Technical Specifications



Description

FL 252 is a tire suitable for hay harvesting applications with rotor rakes/tedders as well as for logistic operations using forklifts. This tire provides excellent durability while the specific tread pattern ensures maximum stability during lifting operations.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Rotor Rake / Tedder
Industrial: Forklift

Version	STANDARD
Type	TT
Tyre Size	5.00 - 8

Dimensions US Standard

Usa code	94006830
Ply Rating	10
Section Width (inch)	5.4
Overall Diameter (inch)	18.9
Rim Rec	3.00 D
Rim Alt	3.25 I

Load capacity (lbs)

	mph / psi	145
15 LOAD WHEEL		3120
15 STEER WHEEL		2405
5 OTHER VEHICLES		3120
15 OTHER VEHICLES		2405
STATIC SIDE LOADER		3625

Printed on 4/17/2024 1:11 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..