

FL 630 SUPER - Technical Specifications



Description

FL 630 SUPER is a flotation tire suitable for field and road applications with trailers, tankers and spreaders. Its resistant structure provides excellent traction and perfect grip even in bends and when maneuvering, while a reinforced bead and steel belts ensure enhanced durability.

UM

International Standard

Construction



RADIAL

Machinery

Agriculture: Spreader • Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	600/55 R 22.5
LI/SS	162 D

Dimensions International Standard

Section Width (mm)	595
Overall Diameter (mm)	1232
Static Loaded Radius (mm)	560
Rolling Circumference (mm)	3757
SRI (mm)	575
Rim Rec	AG 20.00
ECE	E11-106R-004759

Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1580	1775	2210	2510	2900	3290	3590	3940	4325
65	1735	1950	2425	2755	3185	3610	3945	4325	4750
50	2100	2360	2935	3335	3855	4370	4775	5235	5750
40	2360	2650	3295	3750	4330	4910	5365	5880	6460
25	2740	3080	3830	4355	5030	5705	6230	6830	7505
10	3125	3510	4365	4960	5730	6500	7100	7785	8550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 12:37 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..