

FL 637 - Technical Specifications



Description

FL 637 is a radial flotation tire suitable for spreaders, trailers and tankers. The reinforced bead structure provides enhanced durability and higher load capacity. In addition to excellent flotation features leading to reduced soil compaction, this tire shows outstanding self-cleaning properties. The directional tread design ensures excellent traction and enabling speeds up to 70 km/h.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Spreader • Tanker • Trailer

| | |
|-----------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 560/45 R 22.5 |
| LI/SS | 160D |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Section Width (mm) | 544 |
| Overall Diameter (mm) | 1076 |
| Static Loaded Radius (mm) | 501 |
| Rolling Circumference (mm) | 3324 |
| SRI (mm) | 525 |
| Rim Rec | AG 16.00 |
| ECE | E11-106R-008660 |

Load capacity (Kg)

| km/h / bar | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 4.5 | 5.0 | 5.5 | 6.0 |
|------------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 70 | 990 | 1320 | 1650 | 1860 | 2145 | 2435 | 2685 | 2930 | 3220 | 3425 | 3630 | 3880 | 4125 |
| 65 | 1080 | 1440 | 1800 | 2025 | 2340 | 2655 | 2925 | 3195 | 3510 | 3735 | 3960 | 4230 | 4500 |
| 50 | 1310 | 1745 | 2180 | 2455 | 2835 | 3215 | 3540 | 3870 | 4250 | 4520 | 4795 | 5120 | 5445 |
| 40 | 1470 | 1960 | 2450 | 2755 | 3185 | 3615 | 3980 | 4350 | 4775 | 5080 | 5390 | 5755 | 6120 |
| 30 | 1635 | 2175 | 2720 | 3060 | 3535 | 4010 | 4420 | 4825 | 5305 | 5640 | 5980 | 6390 | 6795 |
| 25 | 1710 | 2280 | 2845 | 3200 | 3700 | 4195 | 4625 | 5050 | 5550 | 5905 | 6260 | 6685 | 7110 |
| 10 | 1945 | 2595 | 3240 | 3645 | 4215 | 4780 | 5265 | 5755 | 6320 | 6725 | 7130 | 7615 | 8100 |

Printed on 4/23/2024 3:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..