

FL 639 - Data Sheet



Description

FL 639 is a field-oriented flotation radial tire also suitable for spreading applications. Its wide footprint area ensures low soil compaction resulting in increased crop productivity. The reinforced bead and the sidewall protection contribute to an extended tire life-cycle. FL 639 ensures extraordinary traction along with great self-cleaning properties.

UM

US Standard

Construction



Machinery

Agriculture: Spreader

| SIZE | Version | USACode | LI/SS | LI/SS DRIVE WHEEL | LI/SS FREE ROLLING | RIM REC | RIM ALT | SW | OD | SLR | RC | Туре | ECE |
|------------------|----------|----------|-------------------|----------------------|-----------------------|-------------|------------|------|------|------|-------|------|--------------------------|
| 560/45 R 22.5 | STANDARD | 94034260 | 152 D/163 A8 | | | AG 16.00 | | 21.4 | 42.4 | 19.1 | 130 | TL | E4-106R- 000627 |
| 600/50 R 22.5 | STANDARD | 94063239 | 168 B/156 B | 156 B | 168 B | AG 20.00 | | 24.1 | 46.1 | 20.5 | 141.4 | TL | E11- 106R- 006478 |
| 600/50 R 22.5 | STANDARD | 94028153 | 159 D/170 A8 | | | AG 20.00 | | 24.1 | 46.1 | 20.9 | 139.4 | TL | E4-106R- 000802 |
| 710/40 R 22.5 | STANDARD | 94063246 | 170 B/158 B | 158 B | 170 B | AG 24.00 | | 28.6 | 44.9 | 19.8 | 137.5 | TL | E11- 106R- 006479 |
| 710/40 R 22.5 | STANDARD | 94041176 | 161 D/172 A8 | | | AG 24.00 | | 28.6 | 44.9 | 19.8 | 137.5 | TL | E4-106R- 000801 |
| 800/40 R 22.5 | STANDARD | 94513420 | 168D/178A8 | | | AG 28.00 | | 32.6 | 47.7 | 21.2 | 143.4 | TL | E11- 106R- 0010830 |
| 850/40 R 26.5 | STANDARD | 94064779 | 173 D / 184 A8 | | | AG 28.00 | | 33.9 | 53.3 | 23.6 | 162.3 | TL | E11- 106R- 006228 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/7/2025 7:21 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..