

FL 695 - Technical Specifications



Description

FL 695 has been specifically designed for trailers in construction and transport applications with a unique center block tread pattern. Thanks to its strong casing, FL 695 can carry heavy loads maintaining stability in all conditions and its deep tread ensures optimal self-cleaning during on and off-road applications. Multiple steel cord layers reinforce this pattern against punctures.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Trailer

Industrial: Trailer

Version	STEEL BELTED
Type	TL
Tyre Size	650/55 R 26.5
LI/SS	178 D

Dimensions International Standard

Section Width (mm)	630
Overall Diameter (mm)	1390
Static Loaded Radius (mm)	630
Rolling Circumference (mm)	4242
SRI (mm)	675
Rim Rec	AG20.00
Rim Alt	AG22.00
ECE	E11-106R-007052

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0	5.5	6.0
65	--	--	--	3375	3900	4425	4875	5325	5850	6225	6600	7050	7500
50	--	--	--	4085	4720	5355	5900	6445	7080	7535	7990	8535	9075
40	--	3370	4185	4590	5305	6020	6630	7245	7960	8470	8980	9590	10200
30	2835	3740	4645	5100	5890	6685	7365	8045	8835	9400	9970	10650	11325
25	2965	3915	4860	5335	6165	6995	7705	8415	9245	9840	10430	11140	11850
20	3095	4085	5075	5570	6435	7305	8045	8790	9655	10275	10890	11635	12375
10	3375	4455	5535	6075	7020	7965	8775	9585	10530	11205	11880	12690	13500

Printed on 3/26/2023 4:58 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..