

FLOTATION RIB 774 - Technical Specifications



Description

FLOTATION RIB 774 is suitable in all free-rolling applications, hay harvesting applications and ideal for trailers. It has been designed to provide best handling comfort optimizing the timing of operations as well as high load capacity and a longer tire life.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Harvester • Hay Harvester • Trailer

Version	STANDARD
Type	TL
Tyre Size	600/55 - 22.5
LI/SS FREE ROLLING	169 A8/166 B

Dimensions International Standard

Ply Rating	16
Section Width (mm)	600
Overall Diameter (mm)	1230
Static Loaded Radius (mm)	540
Rolling Circumference (mm)	3716
Rim Rec	AG 20.00
ECE	E11-106R-005944

Load capacity (Kg)

km/h / bar	2.20	2.40	2.60
10 FR	7365	7750	8120
20 FR	6630	6975	7310
30 FR	5890	6200	6495
40 FR	5260	5535	5800
50 FR	4735	4980	5300

Printed on 4/24/2024 9:16 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..