

FLOTATION V LINE - Technical Specifications



Description

FLOTATION V LINE has been specially designed for trailers in transport applications. It shows high flotation capability and ensures low soil compaction protecting the field. FLOTATION V LINE allows you to carry high loads at low pressure maximizing your business productivity.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Trailer

| | |
|--------------------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 500/60 - 22.5 |
| LI/SS DRIVE WHEEL | 151 A8/ 148 B |
| LI/SS FREE ROLLING | 163 A8/159 B |

Dimensions International Standard

| | |
|----------------------------|----------------|
| Ply Rating | 16 |
| Section Width (mm) | 500 |
| Overall Diameter (mm) | 1170 |
| Static Loaded Radius (mm) | 510 |
| Rolling Circumference (mm) | 3489 |
| Rim Rec | AG 16.00 |
| Rim Alt | 15.00 ; 17.00 |
| ECE | E4-106R-001562 |

Load capacity (Kg)

| km/h / bar | 2.80 | 3.00 | 3.20 |
|------------|------|------|------|
| 10 FR | 6315 | 6575 | 6825 |
| 20 FR | 5685 | 5915 | 6145 |
| 30 FR | 5050 | 5260 | 5460 |
| 40 FR | 4510 | 4695 | 4875 |
| 50 FR | 4060 | 4225 | 4375 |
| 10 DW | 4465 | 4650 | 4830 |
| 20 DW | 4020 | 4185 | 4345 |
| 30 DW | 3575 | 3720 | 3865 |
| 40 DW | 3190 | 3320 | 3450 |
| 50 DW | 2870 | 2990 | 3150 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/11/2024 10:54 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..