

FORESTLAND - Data Sheet



Description

FORESTLAND is BKT's latest and innovative agro-forestry pattern. This bias tire has been specifically designed for heavy-duty service in forestry applications but, it can also be employed in some agricultural operations such as landscaping and light mulching.

FORESTLAND is a particularly robust tire thanks to its strong polyester casing. Moreover, the special cut-and-chip resistant tread compound along with the strong sidewall ensure a long tire life even under the harshest operating conditions.

Whilst the open shoulder design provides excellent traction on loose soil, the particular tread pattern and its stiff and reinforced lugs stand for good grip in any soil along with top self-cleaning properties. In addition, the strong bead construction ensures a high level of stability in heavy-duty operations.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tractor

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
14.9 - 28	STANDARD	LS2	140 A8 / 137 B	14	W 13	W 12, W 11	378	1365	0	0	650	TT	
18.4 - 38	STANDARD	LS2	155 A8 / 152 B	14	W 16 L	W 15 L	467	1750	813	5384	825	TT	E11-106R-008167

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/4/2024 2:16 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..