

JUMBO TRAX HD - Technical Specifications



Description

JUMBO TRAX HD is a block pattern tire for skid steers. It features cut and chip resistance and is particularly suitable for heavy-duty service. The deep tread along with excellent sidewall protection provides an extended tire life-cycle. JUMBO TRAX HD is also available in a “special” version.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Skid Steer

Version	STANDARD
Type	TL
Tyre Size	12 - 16.5

Dimensions US Standard

Usa code	94017294
Ply Rating	10
Section Width (inch)	12.8
Overall Diameter (inch)	33.7
Static Loaded Radius (inch)	15.2
Rolling Circumference (inch)	99.3
Rim Rec	9.75
ECE	E11-106R-005563

Load capacity (lbs)

mph / psi	65
5	5600
10	4420
15	4090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 9:48 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..