

LOADER SPECIAL - Data Sheet

Description

LOADER SPECIAL (L-5) is a bias-ply tire that keeps your loaders on the move and provides top efficiency in heavy-duty rock operations. Optimum traction and exceptional cut resistance will boost productivity.



UM

US Standard

Construction

 BIAS

Machinery

OTR: Dozer • Loader

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
20.5 - 25	STANDARD	94069958	L5	20	17.00/2.0		20.9	61.8	0	0	TL
26.5 - 25	STANDARD	94050406	L5	32	22.00/3.0		27	71.5	32.8	211.5	TL
26.5 - 25	STANDARD	94034536	L5	28	22.00/3.0		27	71.5	32.8	211.5	TL
29.5 - 25	STANDARD	94050413	L5	32	25.00/3.5		30.3	76	34.8	226.5	TL
29.5 - 25	STANDARD	94034734	L5	28	25.00/3.5		30.3	76	34.8	226.5	TL
35/65 - 33	STANDARD	94035991	L5	42	28.00/3.5		35.8	82.9	38.4	256.1	TL
40/65 - 39	STEEL BELTED	94075454	L5	56	32.00/4.0		39.4	94.7	0	0	TL
45/65 - 45	STEEL BELTED	94056903	L5	58	36.00/4.5		46.7	109.6	0	0	TL

Printed on 4/25/2024 3:26 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..