

MAGLIFT PREMIUM - Data Sheet



Description

MAGLIFT PREMIUM is a solid tire specially designed for heavy forklift operations in port, mining or scrap yard applications. The extra deep tread (25% more compared to the standard version) with its aggressive and robust pattern provides outstanding front and lateral traction in addition to excellent steering control. The unique tread compound ensures high cut and chip resistance resulting in an extended tire life-cycle. Additional features are low rolling resistance and a smooth run.

UM

US Standard

Construction

◆ SOLID

Machinery

Industrial: Forklift

SIZE	Version	USACode	RIM REC	RIM ALT	SW	OD	Type
6.00 - 9	LIP	94055609	4.00 E - 9		5.4	21.1	
6.00 - 9	LIP NON MARKING	94055906	4.00 E - 9		5.4	21.1	
6.00 - 9	STANDARD	94054299	4.00 E - 9		5.4	21.1	
6.00 - 9	STANDARD NON MARKING	94055890	4.00 E - 9		5.4	21.1	
6.50 - 10	LIP	94055319	5.00 F - 10		5.9	22.9	
6.50 - 10	STANDARD	94055302	5.00 F - 10		5.9	22.9	
7.00 - 12	LIP	94055623	5.00 S - 12		6.4	26.1	
7.00 - 12	STANDARD	94055616	5.00 S - 12		6.4	26.1	

Printed on 3/27/2023 1:22 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..